

KST-F915**Features:**

Waterproof IR Camera R+/OSD

◆IR Distance 50-70M

◆Adopting72PCs ϕ 5mm IR Leds

◆Dual glass, no IR diffusion and fog

◆IP66, outdoor installation

◆Focus lens:2.8-12mm,4-9mm,9-22mm



Model	KST-F915-N60	KST-F915-K65	KST-F915-E65	KST-F915-EP70
Image Sensor	1/3" COLOR SONY Super HAD CCD	1/3" COLOR SONY Super HAD CCD	1/3" COLOR SONY EFFIO	1/3" COLOR SONY EFFIO-P
TV System	PAY/NTSC			
Image Resolution	PAL:752(H)×582(V), NTSC:768(H)×494(V)	PAL:976(H)×582(V), NTSC:976(H)×494(V)	PAL:976(H)×582(V), NTSC:976(H)×494(V)	PAL:976(H)×582(V), NTSC:976(H)×494(V)
Horizontal Resolution	600TVL	650 TVL	700 TVL	700TVL
CCD+DSP	639ccd+CP2040	639ccd+K9	673ccd+EFFIO4140	663ccd+EFFIO-P
Digital to Analog	9Bit			
Minimum illuminator	0.1LUX/F1.2			
S/N Ratio	≥48dB	≥58dB		
AES	1/50-1/100,000sec(PAL), 1/60-1/100,000sec(NTSC)			
WDR	D-WDR	D-WDR	D-WDR	SUPPER WDR
DNR	2D-DNR	3D-DNR	2D-DNR	3D-DNR
OSD	OSD	OSD	OSD	OSD
White Balance	ATW/Manual/Auto			
AGC	Auto/Manual/Off			
BLC	ON/OFF			
Gamma Adjusting	0.45			
synchronization System	Internal Synchronization			
Video Output	1.0Vp-p,75Ω			
IR	5mm x 72pcs			
IR Distance	50-70 Meter			
LENS	2.8-12mm			
Voltage	DC12V (9V ~ 15V)			
Operating Enviroment	~ / 10% ~ 95%RH			
Weight	1.9kg/1.6kg			
packing	380*192*140mm			